

KEEN ELECTRIC Chilled Water Fan Coil (Wall Mounted Type)

MODEL			KKG-250	KKG-300	KKG-400	KKG-500	KKG-600
NOMINAL AIR VOLUME	HI SPEED	CFM	250	300	400	500	600
		M3/H	405	510	680	850	1020
	MED SPEED	CFM	210	254	327	441	547
		M3/H	358	432	557	751	930
	LOW SPEED	CFM	192	203	269	361	464
		M3/H	327	346	458	614	790
COOLING CAPACITY	HI SPEED	W	2200	2540	3090	4070	4450
	MED SPEED	W	1540	2040	2620	3730	4180
	LOW SPEED	W	1450	2500	2270	3240	3740
HEATING CAPACITY	HI SPEED	W	3019	3693	4338	5686	6300
	MED SPEED	W	2596	3250	3861	5117	5670
	LOW SPEED	W	2234	2770	3254	4321	4725
WATER FLOW VOLUME		M3/H	0.378	0.454	0.529	0.701	0.766
WATER PRESSURE DROP		Kpa	12	18	22	26	29
ROWS		Qty	2	2	2	2	2
TUBE PITCH * ROW PITCH		Mm	21 * 13.37	21 * 13.37	21 * 13.37	21 * 13.37	21 * 13.37
TUBE DIAMETER		Mm	Φ 7	Φ 7	Φ 7	Φ 7	Φ 7
FIN SPACING		Mm	1.5	1.5	1.5	1.5	1.5
COIL DIMENSION (L * H)		Mm	635 * 315	635 * 315	635 * 315	785 * 315	785 * 315
FAN MOTOR QUANTITY		Qty	1	1	1	1	1
FAN MOTOR INPUT		W	23 / 21 / 20	41 / 33 / 27	41 / 33 / 27	44 / 42 / 39	44 / 42 / 39
NOISE LEVEL (HI & MED)		Db (A)	30 (28)	35 (32)	35 (32)	38 (35)	38 (35)
INLET / OUTLET PIPE (INTERNAL		Inch	3/4	3/4	3/4	3/4	3/4
DRAIN PIPE (EXTERNAL THREAD)		Inch	3/4	3/4	3/4	3/4	3/4
WEIGHT	NET	Kg	12	12	12	15	15
	GROSS	Kg	16	16	16	19	19
DIMENSION (W * H * D)	NET	Mm	915 * 210 * 290	915 * 210 * 290	915 * 210 * 290	915 * 210 * 290	915 * 210 * 290
	PACKING	Mm	1020 * 300 * 385	1020 * 300 * 385	1020 * 300 * 385	1020 * 300 * 385	1020 * 300 * 385
CONTROL TYPE			WIRED CONTROL				