

## KEEN ELECTRIC CHILLED WATER FANCOIL (FOUR WAY CASSETTE TYPE)

MODEL		KKA-600R (A)	KKA-750R (A)	KKA-850R (A)	KKA-950R (A)	KKA-1200R (A)	KKA-1500R (A)	
NOMINAL AIR VOLUME	HI SPEED	CFM	600	750	850	950	1200	1500
		M <sup>3</sup> /H	1020	1275	1445	1615	2040	2550
	MED SPEED	CFM	454	542	716	809	1011	1264
		M <sup>3</sup> /H	772	922	1218	1376	1720	2150
	LOW SPEED	CFM	352	421	600	678	847	1058
		M <sup>3</sup> /H	600	717	1020	1153	1440	1800
COOLING CAPACITY	HI SPEED	W	5.73	7.01	7.28	8.25	10.38	12.89
	MED SPEED	W	4.73	5.62	6.46	7.39	9.25	11.51
	LOW SPEED	W	3.96	4.72	5.71	6.54	8.2	10.21
HEATING CAPACITY	HI SPEED	W	7.83	9.36	11.22	12.27	14.77	17.6
	MED SPEED	W	6.89	8.14	9.64	10.79	12.7	15.48
	LOW SPEED	W	5.09	6.1	7.23	8.2	9.39	11.61
WATER FLOW VOLUME		M <sup>3</sup> /H	0.98	1.2	1.25	1.41	1.78	2.21
WATER PRESSURE DROP		Kpa	23.8	25.2	27	30	44	46
ELRCTRICAL AUXILIARY HEATER		W	2100	2100	2700	2700	2700	2700
tROWS		Qty	2	2	2	2	2	2
TUBE PITCH * ROW PITCH		Mm	21 * 13.37	21 * 13.37	21 * 13.37	21 * 13.37	21 * 13.37	21 * 13.37
TUBE DIAMETER		Mm	Φ 7	Φ 7	Φ 7	Φ 7	Φ 7	Φ 7
FIN SPACING		Mm	1.5	1.5	1.5	1.5	1.5	1.5
COIL DIMENSION ( L * H )		Mm	1960 * 168	1960 * 168	1960 * 252	1960 * 252	1960 * 252	1960 * 252
FAN MOTOR QUANTITY		Qty	1	1	1	1	1	1
FAN MOTOR INPUT		W	110	110	143	143	143	143
NOISE LEVEL ( HI & MED )		Db ( A )	45 ( 43 )	46 ( 43 )	47 ( 45 )	48 ( 45 )	49 ( 46 )	49 ( 47 )
INLET / OUTLET PIPE ( INTERNAL THREAD )		Inch	3/4	3/4	3/4	3/4	3/4	3/4
DRAIN PIPE ( EXTERNAL THREAD )		Inch	3/4	3/4	3/4	3/4	3/4	3/4
WEIGHT	NET / GROSS ( UNIT )	Kg	29 / 36	29 / 36	35 / 42	35 / 42	35 / 42	35 / 42
	NET / GROSS ( PANEL )	Kg	6 / 9	6 / 9	6 / 9	6 / 9	6 / 9	6 / 9
DIMENSION ( W * H * D )	NET ( UNIT )	Mm	840 * 230 * 840	840 * 230 * 840	840 * 300 * 840	840 * 300 * 840	840 * 300 * 840	840 * 300 * 840
	NET ( PANEL )	Mm	950 * 46 * 950	950 * 46 * 950	950 * 46 * 950	950 * 46 * 950	950 * 46 * 950	950 * 46 * 950
	PACKING ( UNIT )	Mm	955 * 247 * 955	955 * 247 * 955	955 * 317 * 955	955 * 317 * 955	955 * 317 * 955	955 * 317 * 955
	PACKING ( PANEL )	Mm	1035 * 90 * 1035	1035 * 90 * 1035	1035 * 90 * 1035	1035 * 90 * 1035	1035 * 90 * 1035	1035 * 90 * 1035
CONTROL TYPE		WIRED CONTROL						